

07-27-00

A

UTILITY PATENT APPLICATION TRANSMITTAL
(Large Entity)*(Only for new nonprovisional applications under 37 CFR 1.53(b))*Docket No.
CX099034

Total Pages in this Submission

21

TO THE ASSISTANT COMMISSIONER FOR PATENTSBox Patent Application
Washington, D.C. 20231

Transmitted herewith for filing under 35 U.S.C. 111(a) and 37 C.F.R. 1.53(b) is a new utility patent application for an invention entitled:

HIGH AVAILABILITY MECHANISM IN A CABLE ENVIRONMENT

and invented by:

Robert WALLACEIf a **CONTINUATION APPLICATION**, check appropriate box and supply the requisite information:☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No.: _____

Which is a:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No.: _____

Which is a:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No.: _____

Enclosed are:

Application Elements

1. ☒ Filing fee as calculated and transmitted as described below
2. ☒ Specification having 12 pages and including the following:
 - a. ☒ Descriptive Title of the Invention
 - b. ☐ Cross References to Related Applications *(if applicable)*
 - c. ☐ Statement Regarding Federally-sponsored Research/Development *(if applicable)*
 - d. ☐ Reference to Microfiche Appendix *(if applicable)*
 - e. ☒ Background of the Invention
 - f. ☒ Brief Summary of the Invention
 - g. ☒ Brief Description of the Drawings *(if drawings filed)*
 - h. ☒ Detailed Description
 - i. ☒ Claim(s) as Classified Below
 - j. ☒ Abstract of the Disclosure

UTILITY PATENT APPLICATION TRANSMITTAL (Large Entity)

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Docket No.
CX099034

Total Pages in this Submission
21

Application Elements (Continued)

3. ☒ Drawing(s) (when necessary as prescribed by 35 USC 113)

- a. ☐ Formal Number of Sheets _____
- b. ☒ Informal Number of Sheets 3

4. ☒ Oath or Declaration

- a. ☒ Newly executed (original or copy) ☐ Unexecuted
- b. ☐ Copy from a prior application (37 CFR 1.63(d)) (for continuation/divisional application only)
- c. ☒ With Power of Attorney ☐ Without Power of Attorney
- d. ☐ DELETION OF INVENTOR(S)
Signed statement attached deleting inventor(s) named in the prior application,
see 37 C.F.R. 1.63(d)(2) and 1.33(b).

5. ☐ Incorporation By Reference (usable if Box 4b is checked)

The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under Box 4b, is considered as being part of the disclosure of the accompanying application and is hereby incorporated by reference therein.

6. ☐ Computer Program in Microfiche (Appendix)

7. ☐ Nucleotide and/or Amino Acid Sequence Submission (if applicable, all must be included)

- a. ☐ Paper Copy
- b. ☐ Computer Readable Copy (identical to computer copy)
- c. ☐ Statement Verifying Identical Paper and Computer Readable Copy

Accompanying Application Parts

8. ☒ Assignment Papers (cover sheet & document(s)) **copy of the executed Assignment**

9. ☐ 37 CFR 3.73(B) Statement (when there is an assignee)

10. ☐ English Translation Document (if applicable)

11. ☐ Information Disclosure Statement/PTO-1449 ☐ Copies of IDS Citations

12. ☐ Preliminary Amendment

13. ☒ Acknowledgment postcard

14. ☒ Certificate of Mailing

☐ First Class ☒ Express Mail (Specify Label No.): EK 129 212 830 US

UTILITY PATENT APPLICATION TRANSMITTAL
(Large Entity)

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Docket No.
CX099034

Total Pages in this Submission

21

Accompanying Application Parts (Continued)

15. ☐ Certified Copy of Priority Document(s) (if foreign priority is claimed)


16. ☐ Additional Enclosures (please identify below):

Fee Calculation and Transmittal

CLAIMS AS FILED

For	#Filed	#Allowed	#Extra	Rate	Fee
Total Claims	9	- 20 =	0	x \$18.00	\$0.00
Indep. Claims	2	- 3 =	0	x \$78.00	\$0.00
Multiple Dependent Claims (check if applicable) <input type="checkbox"/>					\$0.00
BASIC FEE					\$690.00
OTHER FEE (specify purpose)					\$0.00
TOTAL FILING FEE					\$690.00

- ☒ A check in the amount of **\$690.00** to cover the filing fee is enclosed.
- ☒ The Commissioner is hereby authorized to charge and credit Deposit Account No. **50-0369** as described below. A duplicate copy of this sheet is enclosed.
- ☐ Charge the amount of _____ as filing fee.
- ☒ Credit any overpayment.
- ☒ Charge any additional filing fees required under 37 C.F.R. 1.16 and 1.17.
- ☐ Charge the issue fee set in 37 C.F.R. 1.18 at the mailing of the Notice of Allowance, pursuant to 37 C.F.R. 1.311(b).


Signature
David D. Lowry (Reg. No. 38,538)
BROWN RUDNICK FREED & GESMER, PC
One Financial Center
18th Floor, BOX IP
Boston, MA 02111

Dated: July 26, 2000

CC:


CERTIFICATE OF MAILING BY "EXPRESS MAIL" (37 CFR 1.10) Applicant(s): Robert Wallace	Docket No. CX099034
--	-------------------------------

Serial No. not yet assigned	Filing Date July 26, 2000	Examiner not yet assigned	Group Art Unit not yet assigned
---------------------------------------	-------------------------------------	-------------------------------------	---

Invention: **HIGH AVAILABILITY MECHANISM IN A CABLE ENVIRONMENT**

I hereby certify that this **Utility Patent Appl (Spec.: 12 pp; drawings: 3 pp) executed decl.; copy of exec. assignment; filing fee; transmittals.** *(Identify type of correspondence)*
is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 in an envelope addressed to: The Commissioner of Patents and Trademarks, Washington, D.C.
20231-0001 on July 26, 2000
(Date)

Carmen M. Constantinescu
(Typed or Printed Name of Person Mailing Correspondence)


(Signature of Person Mailing Correspondence)

EHK 129 212 830
("Express Mail" Mailing Label Number)

Note: Each paper must have its own certificate of mailing.

Docket Number: CX099034
BRFG Docket: 20368/7

Application for U.S. Patent:

HIGH AVAILABILITY MECHANISM IN A CABLE ENVIRONMENT

Inventor:

Robert Wallace

of

Motorola Corporation

5 HIGH AVAILABILITY MECHANISM IN A CABLE ENVIRONMENT

BACKGROUND OF THE INVENTION

The present invention relates to headend devices and more particularly to devices for providing high availability and fault tolerance in a cable system.

10 Cable communication systems typically route signals from a headend through trunk cables or fibers from which cables branch to individual users. The headend is the originating point in a communication system. Demand for connections through cable headends has greatly increased as cable usage has increased. Increased usage of cable modems and cable telephony is expected to place further demand upon headend operators. Cable headends therefore require
15 high availability platforms having maximum fault tolerance for routing signals.

Providing a high availability platform in a cable headend environment is difficult. Typical cable headend units have multiple headend elements, each driving a separate cable wire. Physical limitation on the length of cable wire which can be driven by one headend element requires cable networks to be divided into smaller connection networks, each driven by a
20 separate headend element. Even within these limits, cable headend units suffer high burnout, in part due to the power requirements and heat generated from driving a radio frequency (RF) signal. Failures often suddenly occur without prior indication, thereby causing an interruption in service. Typical radio frequency (RF) interfaces at a cable headend are switched using RF matrix switches which are well known to persons of ordinary skill in the art. Fault tolerance is

achieved by using a matrix switch to transfer signals from a failed cable element to a good element. Any number of spare elements are typically provided for any set of cable elements that are attached to the matrix switch. A failed element is switched out when a fault is detected and an appropriate spare element is switched into its place while the fault is swapped out or repaired.

5 Fault tolerant systems have been developed to provide a single spare element which is capable of taking on the role of any one of a set of other elements in the cable headend. The number of spare elements and switching interfaces is reduced, thereby reducing cost and space requirements. Such fault tolerant systems are not scalable because they are typically switched using matrix switches which are available only in fixed $N \times N$ configurations. Incremental
10 addition of a single spare element or a small number of spare elements in such systems may therefore require the expensive purchase and installation of a large matrix switch. Scalability is thus limited to installation of new element in blocks based on added switch matrixes.

BRIEF SUMMARY OF THE INVENTION

15 Accordingly, the present invention provides an apparatus and method for efficiently replacing failed elements in a cable headend. Each cable element in a fault tolerant cable headend system is configured to serve as a spare for at least one of its adjacent elements. Upon the failure of any element, an adjacent element is switched into the circuit of the failed element. The next adjacent element is switched into the circuit of the first adjacent element to take its
20 place. A rippling sequence of shifting elements propagates until a spare unused element is switched into its neighbors place. The failed element may then be repaired or replaced (swapped out) and becomes a spare element, or the elements are shifted to their original position. No further switching is required until another failure occurs.

Switching may be implemented according to the present invention by using simple multiplexing devices. Each RF switch or multiplexing device may be installed as an individual module. A systems according to the present invention is therefore scalable to very large configurations in an economical and nearly linear manner.

5 The system according to the present invention is useful for applications where each elements is capable of performing the function of the adjacent elements that it may be called upon to replace. State information (if any) for an element should be available for at least one adjacent element. A system according to the present invention may be implemented using 3 to 1 multiplexing devices wherein any element is capable of replacing either of its adjacent elements.

10 Advantages of the present invention include automatic fault tolerance in a system which may be easily scaled up or down. A system according to the present invention also requires minimal real estate for extra components such as spare boards. Other advantages include simplicity in monitoring and fail over, in that an element need only monitor the functioning and state of an adjacent element, without a need for centralized monitor. Other advantages include
15 ease of repair by technicians in that only a failed board in a system need be pulled out and replaced, instead of having to pull out several boards for reconfiguration.

BRIEF DESCRIPTION OF THE DRAWINGS

20 Fig. 1 is a block diagram of a system according to the present invention;

Fig. 2a is a block diagram showing an illustrative embodiment according to the present invention;

Fig. 2b is a block diagram showing how the illustrative embodiment in Fig. 2a

compensates for a failed element;

Fig. 2c is a block diagram showing the illustrative embodiment of Fig. 2b after the failed element has been repaired or replaced; and

Fig. 2d is a block diagram showing how the illustrative embodiment of Fig. 2c
5 compensates after another element has failed.

DETAILED DESCRIPTION OF THE INVENTION

Fig. 1 shows a typical system according to the present invention including a headend
10 element 14 and a switch 10. The headend element 14 is any type of transmitting or receiving unit used in a system where multiple similar headend elements 14 are in connection with separate circuits or networks 16. Examples include RF cable transmitters or receivers, ethernet or ATM drivers, optical drivers, repeaters, telephone circuits or terminators, modems including telephonic or cable, etc. Such elements 14 are typically on PC boards mounted close together in a backplane system. The switch 10 is any type of switch which selects between two (or more)
5 connections, including relays, both mechanical and solid state, and multiplexers or demultiplexers. A headend element 14a is connected to one input of one switch or multiplexing device 10a and an adjacent headend element 14b is connected to another input of the multiplexing device 10a. The multiplexing device 10a is switchable to connect a line 16 to either of two adjacent headend elements 14, as shown by arrow 13.

20 Each element 14 has access to state information 15 regarding an adjacent element 14 that is connected to another input on a shared multiplexing device 12, as shown by arrow 17. State information 15 (if any) may be accessible either by maintaining individual element 14 state information in a centralized location separate from the elements 14 (not shown), or by providing

element 14 with appropriate storage for both its own state information 15, and for its adjacent neighbor. Each element 14 is thereby continuously prepared to be swapped into a role of an adjacent element 14.

Upon detection of a fault in any headend element 14 according to the present invention, the switch 10 is signaled to switch over so the adjacent element 14 is now driving the line 16 connections over to an adjacent element 14 in the direction of the nearest spare element. The elements 14 participating in a shift then refresh their status information in preparation for a later shift.

The failed element 14 may then be repaired or replaced to serve as the next spare element 18. Alternatively the system may shift back to employ the repaired or replaced element 14 and disconnect the original spare element 18.

Referring to Fig. 2a, an exemplary embodiment for a cable headend system according to the present invention is illustrated. The RF switch 10 includes a cascaded set of five 2-1 multiplexing devices 12. The RF switch 10 of the exemplary embodiment connects five elements 14 in a cable headend to five cable outputs 16 and includes one spare element 18. It can be seen by reference to the Fig. 2a that the multiplexing devices 12 are modular so that any number of multiplexing devices 12 may be cascaded to switch a corresponding number of elements 14. It will be apparent to persons of skill in the art that 3-1 multiplexing devices may be used in place of the 2-1 multiplexing devices 12 of the illustrated exemplary embodiment of Fig. 2a - Fig. 2d.

The 2-1 multiplexing devices 12 may be switched to connect any cable output 16 to any of two headend elements 14. Accordingly each 2-1 multiplexing devices 12 provide a connections from a single cable output to a single headend element 14 or its adjacent element 14

on one side. Systems according to the present invention that employ 3-1 multiplexing devices are capable of switching a single cable output 16 from a single headend element 14 to either of its two adjacent elements 14.

Referring now to Fig. 2b, the condition of the exemplary embodiment is illustrated after a failure of a single element 14' has occurred. Upon detection of the failure, the 2-1 multiplexing devices 12 for the failed element 14' switches over so the adjacent element 14 takes over driving the cable output of the failed element 14'. Either simultaneously, or in a ripple fashion, the 2-1 multiplexing devices 12 for each adjacent element 14 switches over until all cable outputs 16 are driven, with the spare element 18 now filling in for its adjacent element 14. It can be seen that three of the 2-1 multiplexing devices 12 have changed state to shift connections of three cable outputs 16 to adjacent elements. Each element 14 from the failed element 14' to the spare element 18 is functionally replaced by the element 14 to its left.

Referring now to Fig. 2c, the condition of the exemplary embodiment is illustrated after the failed element 14' of Fig. 2b, is repaired or replaced. The repaired or replaced element becomes the new spare element 18. Alternatively, the 2-1 multiplexing devices 12 all switch back to their original settings, whereupon the end element 14 will again be the spare, as shown in Fig. 2a. However, it is not necessary to "reset" the system in this way, as will be described.

Referring to Fig. 2d, the condition of the exemplary embodiment of Fig. 2c is illustrated after a second failure has occurred, this time in element 14' Fig. 2d. It can be seen that two 2-1 multiplexing devices 12 are switched back to their initial state thereby cascading two cable outputs 16 toward the right and connecting them to good elements 14. A feature of the present invention is that as elements 14 fail and are replaced, the position of the spare element 18 can

move around the system, and the 2-1 multiplexing devices 12 will always be able to configure the system so that all cable outputs 16 are driven.

The control of monitoring the system switching headend elements 14 may be performed by a separate monitoring and control system (not shown), or may be performed in a autonomous fashion by the individual headend elements 14. This autonomous monitoring ability as a useful feature of the present invention. All a headend element 14 has to do is know the state (status information) of it's adjacent element 14 (which can be determined by noting which element 14 it would replace if the switch device 12 switches over), and if it's adjacent element 14 is responding. If the adjacent element 14 stops responding, then the headend element 14 informs the switch device 12 to switch over, and updates it's state to be that of the failed adjacent element 14. The headend element finally stops responding to its neighbor's 14 monitoring, thereby causing the neighbor 14 to perform this same switchover, thereby rippling down the system until the spare element 18 is reached. Therefore, the system can shift over autonomously, without the need for central monitoring and control. The spare element 18 monitors the state 15 of its adjacent element 14, the only difference is that the spare element 18 is offline until it is switched in and takes over for its adjacent element.

If a higher level of fault tolerance is desired, then 3-1 multiplexing devices 12 can be employed, whereby a failed element 14' can be replaced an adjacent element on either side (not shown). The advantage to this configuration of the present invention is two (or more) spare elements 18 may be used, with the spare elements 18 initially positioned at either end of the system. This configuration of the present invention allows for multiple element 14 failures. Both spare elements 18 may then move around the system, which has higher reliability because multiple elements 14 can fail before the system must be serviced.

Any number of modular multiplexing devices 12 are cascaded to form an RF switch 12 for a fault system at a cable headend. Each element 14 is capable of performing the functions of at least one adjacent element 14 and stores relevant status information regarding the at least one adjacent element 14 to facilitate rapid substitution when a failure of an element 14 occurs.

- 5 Multiplexing devices 12 may be added or removed in a modular fashion to facilitate scaling of the system.

In at least one embodiment of the present invention, a cable headend element is a cable modem termination system such as a model CAS 2000 produced by Motorola Corporation. It should be apparent to persons of skill in the art that any number of headend elements may be
10 switched according to the present invention to provide a low cost scalable fault tolerance system. Persons having ordinary skill in the art will recognize that an RF switch 10 according to the present invention may also be manually or automatically controlled to disconnect an element 14 and shift specific output cables 16 toward a spare element 18. The invention may thereby be used to facilitate routine maintenance operations as well as to provide fault tolerance.

- 15 Although exemplary embodiments have been described, other embodiments and modifications of the invention are intended to be covered by the spirit and scope of the appended claims.

CLAIMS

I claim:

1) A fault tolerant headend system comprising:

at least two headend elements, a first headend element and an adjacent headend element;

5 at least one switching device having an output port capable of connecting to one of at least two inputs ports wherein one input port is connected to said first headend elements and another input port is connected to said adjacent headend element;

wherein said output port of each switching device is connectable to an output cable;

wherein said adjacent headend element is capable of taking over functioning of said first

10 headend element; and

at least one of said headend elements is a spare headend element.

2) The system according to claim 1 wherein a plurality of said switching devices are configurable in modular fashion wherein individual switching devices are installable and
15 removable to scalably configure capacity.

3) The system according to claim 1 wherein said headend system is a cable headend system.

20 4) The system according to claim 1 wherein each of said switching devices is a 2 to 1 switching device having two input ports and one output port.

5) The system according to claim 1 wherein each of said switching devices is a 3 to 1 switching device having three input ports and one output port.

6) The system according to claim 1 wherein said first headend element includes state information; said state information accessible by said adjacent headend element.

7) The system according to claim 1 further including a plurality of headend elements arranged in a row, wherein if one headend element fails, said switching devices shift at least one headend element so that an adjacent headend element to said failed headend element takes over for said failed headend element; and said spare headend element takes over for a headend element adjacent to said spare headend element.

8) A method of providing a fault tolerant headend system comprising:

connecting a plurality of adjacent headend elements to a series of switching devices

wherein at least one of said headend elements is a spare headend element and wherein each headend element is capable of taking over functioning of at least one adjacent headend element;

5 detecting a fault in one of said headend elements;

shifting headend elements, comprising:

configuring a headend element adjacent to said fault detected headend elements to take over functioning of said fault detected headend elements; and

changing a state of specific switching devices to connect said adjacent headend element to an output cable of said fault detected headend elements; and

10 performing said steps of shifting headend elements in the direction of a spare headend element, until the spare element is connected to an output cable.

9) The method according to claim 8 further comprising the steps of refreshing said

15 failed element to serve as a new spare element.

ABSTRACT OF THE DISCLOSURE

A scalable fault tolerant cable headend switching system using modular switching or multiplexing devices. A radio frequency switch connects a series of adjacent cable headend element to a series of output cables. At least one spare cable headend element is connected along
5 with the series. Each cable headend element is configured to be readily swapped with adjacent elements. Output cables are cascaded away from a faulty element toward a spare element when a fault is detected.








Fig. 1





COMBINED DECLARATION AND POWER OF ATTORNEY

As a below named inventor(s), I hereby declare that:

TYPE OF DECLARATION

This declaration is for a utility patent application.

INVENTORSHIP IDENTIFICATION

My residence, post office address and citizenship are as stated below, next to my name. I believe that I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if two or more names are listed below) of the subject matter that is claimed, and for which a patent is sought on the invention entitled:

TITLE OF INVENTION

HIGH AVAILABILITY MECHANISM IN A CABLE ENVIRONMENT

SPECIFICATION IDENTIFICATION

The specification

☒ is attached hereto.

☐ was filed on _____ and has U.S. Application Number _____,
and was amended on _____.

ACKNOWLEDGMENT OF REVIEW OF PAPERS AND DUTY OF CANDOR

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information, which is material to patentability as defined in 37, Code of Federal Regulations, Section 1.56.

PRIORITY

The present application claims the benefit under 35 U.S.C. §119(e) of Prior U.S. Provisional Applications:

Provisional Application Serial Number

Filing Date

The present application claims the benefit under 35 U.S.C. §120 of the following Applications:

Application Serial Number

Filing Date

Status

POWER OF ATTORNEY

I hereby appoint the following practitioner(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith.

APPOINTED PRACTITIONER(S)

CUSTOMER NUMBER 22917

SEND CORRESPONDENCE TO

DIRECT TELEPHONE CALLS TO:

CUSTOMER NUMBER 22917

Joanne Pappas 508 261-4358

DECLARATION

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

SIGNATURE(S)

First Inventor: Robert Wallace

Inventor's signature Robert H. Wallace **Date** 7/24/2000
Country of Citizenship USA
Residence Portsmouth, RI
Post Office Address 104 Redwood Road, Portsmouth, RI 02871

#926159 v1 - lowrydd - %mn011.doc - 20368/6

11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100 101 102 103 104 105 106 107 108 109 110 111 112 113 114 115 116 117 118 119 120 121 122 123 124 125 126 127 128 129 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150 151 152 153 154 155 156 157 158 159 160 161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180 181 182 183 184 185 186 187 188 189 190 191 192 193 194 195 196 197 198 199 200 201 202 203 204 205 206 207 208 209 210 211 212 213 214 215 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305 306 307 308 309 310 311 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400 401 402 403 404 405 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495 496 497 498 499 500 501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600 601 602 603 604 605 606 607 608 609 610 611 612 613 614 615 616 617 618 619 620 621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641 642 643 644 645 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660 661 662 663 664 665 666 667 668 669 670 671 672 673 674 675 676 677 678 679 680 681 682 683 684 685 686 687 688 689 690 691 692 693 694 695 696 697 698 699 700 701 702 703 704 705 706 707 708 709 710 711 712 713 714 715 716 717 718 719 720 721 722 723 724 725 726 727 728 729 730 731 732 733 734 735 736 737 738 739 740 741 742 743 744 745 746 747 748 749 750 751 752 753 754 755 756 757 758 759 760 761 762 763 764 765 766 767 768 769 770 771 772 773 774 775 776 777 778 779 780 781 782 783 784 785 786 787 788 789 790 791 792 793 794 795 796 797 798 799 800 801 802 803 804 805 806 807 808 809 810 811 812 813 814 815 816 817 818 819 820 821 822 823 824 825 826 827 828 829 830 831 832 833 834 835 836 837 838 839 840 841 842 843 844 845 846 847 848 849 850 851 852 853 854 855 856 857 858 859 860 861 862 863 864 865 866 867 868 869 870 871 872 873 874 875 876 877 878 879 880 881 882 883 884 885 886 887 888 889 890 891 892 893 894 895 896 897 898 899 900 901 902 903 904 905 906 907 908 909 910 911 912 913 914 915 916 917 918 919 920 921 922 923 924 925 926 927 928 929 930 931 932 933 934 935 936 937 938 939 940 941 942 943 944 945 946 947 948 949 950 951 952 953 954 955 956 957 958 959 960 961 962 963 964 965 966 967 968 969 970 971 972 973 974 975 976 977 978 979 980 981 982 983 984 985 986 987 988 989 990 991 992 993 994 995 996 997 998 999 1000